

XXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXX

BEST-9050 30W / 50WXXXXXXXXXXXX

□□

XXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXX

XXXXXXXXXXXXXXXXXXXX - XXXXXXXXXXXXXXXXXXXXXXX

XXXXXXXX - XXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXX

XXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXX

□□□□

□□□□□

XX

□□□□

XX

XX

XXXXXXXXXXXXXXXXXXXX2/3XXXXXXXX

XXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXX

XXXXXXXX165 * 85 * 40mm□□/□/□□

XXXXXXXX175 * 95 * 50mm□□/□/□□

XXXXXXXX215 * 170 * 125mm□L / W / H□

N.W□0.65KG G.W□0.85KG

PRODUCT APPLICATION



PRODUCT DISPLAY



PRODUCT SIZE



PRODUCT DETAILS



Model:BST-9050	Power: 30W/50	Voltage: 220V/240V
Volume: 0.5L	Frequency: 40KHz	work time: 8h

- ✓ Transducer with high power and strong effect.
- ✓ The volume is large enough for professional cleaning.
- ✓ With a forced cooling device, which can work very long.
- ✓ Safety circuit design, PCBA curing treatment.
- ✓ Switzerland introduced the advanced technology of elaborate design, using CPU control.
- ✓ Systemic use stainless steel to create, the appearance is very beautiful, high work efficiency, stable performance.
- ✓ Widely used in optical and clock parts, micro bearing, jewelry, medical equipment, electronic PCB board high requirements etc.

PRODUCT PHOTOGRAPH



FRONT



BEHIND



TOP



BOTTOM



PRODUCT PACKAGING

WEIGHT: 785G

