5 6□□□□□□□□□□CR - V□□□□□□□□□□□□□□□□□□□□□□□□□□

□□□□

60□CR-V□□□□□□□□□□□□□3□□□PVC□□□□□□□□□□□□□□□□

□□

□□□

□□□□□□□□□□□

□□

60□□□□□□□□□□

□□□□

□□□□□□

□□□□

□□□

□□□□□□

PVC□□□□□□

□□□□

□□□□□□□□□□□□□□□□□□□□□□□□□

□□□□

□□□□□□□+□□□□□□□□

□□□□

OEM□ODM□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□

□□□□□□□□

□□□□□□□□□□□□□□□□□□□□

□□□

□□

□□□□□□□□□□□□□□□□

IC□□□□□□□□□□□□□□□

□□□□□

□□□□□□□□□□□□□□□□□□□□□□□

□□□□□□□□□

D.I.Y□□□□□□□□□□□□□

PRODUCT DISPLAY

PRODUCT SIZE

Material:high quality alloy steel(60CR-V)

Process:using repeated forging,the surface is polished after grinding and processing by precision machining

Hardness:the overall hardness is HRC38-42 the blade hardness is HRC56-62

Shear capacity:HRC20 below

Hard wire Φ1.5mm

soft copper wire,aluminum wire Φ0.1-2.0mm



PRODUCT DETAILS

Front

Back side





User manual

Warning

This model is not insulated tools. Please use it when power off.

Attention

- To protect user safe, please use protective glasses.
- As the cut material will fly out, make sure no one beside you and no easy damaged things beside you, then begin working.
- This product is not a dedicated pressure equipment.
- When stored, please assure the blade at the closed state and can not be touched by children.
- Do not let the plier tip rub something.
- Please do not directly touch the blade part with hand.
- Do not use in cutting hard materials and steel wire, etc.
- Do not use the pliers above its cutting capability and coarse wire.

PRODUCT PHOTOGRAPH

PRODUCT PACKAGING

WEIGHT:76G

FRONT

75MM

BACK