□□ □□ □□□□ □□ □□, □□ □□ □□ □□ □□ □□, □□ □□ □□ □□ □□ □□

BEST-9050 30W / 50W □□□□□ □□ □□□ □□□ □□□ □□□

□□
□□ □□ □□□□ □□ □□□□□ - □□, □□□, □□□, □□ □
□□ □□□ □□ □□ : □□, □□□ □□, □, □□, □□ □□.
□□ : □ : □□□ □□□ □□, □□ □ □□ □□, □□ □ □□ □□, □□ □□□ □
□□ □□□ □□ □□□ □□□□ □□□□□. □□□□□.

□□□

□□ □□:
□□□ □□□□ □□□□ □□□ □□□□□ □□□ □□□□ □□ □□□□ □□ □□□ □□ □□□ □□□□ □□ □□□□□ □□□□□□. □□□ □□□□□ □□□ □□□□
□□ □□□ □□ □□□□ □□ □□□ □ □□□□.

□□ □□
□□□□ □□ □□□ □ □□ □□ □□□ □□ □□□ □□ □□□ □□□□□ □□□□□□. □□ □□ □□□ □□□ □□ □□□□□ □□ □□□□ □□□□ □□ □□□□□.
□□□ □□ □□ □□ □□□ □□ □□ □ □□□ □□□ □□ □□□ □□□□□□. □□□ □□ □□□ □.
□□ : □□ □□ □□ □□ □□□ 2/3 □□□ □□□□□.
□□ □□□ □□□□ □□□ □□□□ □□ □□ □□ □□ □□□ □□□ □□ □□□□.
□□ (□ □□) : 165 * 85 * 40mm (L / W / H)
□□ (outter □□) : 175 * 95 * 50mm (L / W / H)
□□ □□ : 215 * 170 * 125mm (L / W / H)
N.W : 0.65KG G.W : 0.85KG

PRODUCT APPLICATION

PRODUCT DISPLAY

PRODUCT SIZE

PRODUCT DETAILS

Model:BST-9050	Power： 30W/50	Voltage： 220V/240V
Volume： 0.5L	Frequency：40KHz	work time：8h

- ☑ Transducer with high power and strong effect.
- ☑ The volume is large enough for professional cleaning.
- ☑ With a forced cooling device, which can work very long.
- ☑ Safety circuit design, PCBA curing treatment.
- ☑ Switzerland introduced the advanced technology of elaborate design, using CPU control.
- ☑ Systemic use stainless steel to create, the appearance is very beautiful, high work efficiency, stable performance.
- ☑ Widely used in optical and clock parts, micro bearing, jewelry, medical equipment, electronic PCB board high requirements etc.

PRODUCT PHOTOGRAPH

FRONT

BEHIND

TOP

BOTTOM

PRODUCT PACKAGING

WEIGHT: 785G