□□□□□□ □□□□□□ □ □□□□□□ □□□□□□□ □□□□□□□ □□□□□□ □□□□□ □□□□□ □ □□□ □□□□□□ □□□□□ □□□□ □□□□□
□□□□□□ □□□□□□□ □□□□□ □□□□ □□□□□□□

BEST-9050 30W / 50W □□□□□□ □□□□□□□ □□□ □□□□□□□□ □□□□□□□□ □□□□□□□ □□□□□ □□□□□□□ □□□□□□□

□□□□□
.□□□ □□□□ □□□□ □ □□□□□ □ □□□□□ □ □□□□ - □□□ □□□□□□ □□□□ □□□ □□□□□□ □□□□
□ □□□□□□ □ □□□□□□□ □□□□□□□□ □ □□□□□□□□ □ □□□□□□ □□□□ □□□ :□□□□□□□ □□□□□□ □□ □□□□□□□ □□□□□□□
.□□□□□ □□□□ □ □□□□□□□ □□□□□□
□□□□□□ □□□□ □□□□ □ □□□□□□ □□□□□□□□ □□□□□□□□□ □□□□□□□□□ □□□□□□□ □□□ □ □□□□□□ □□□□ □□□ :□□□□□
.□□□ □□□□□□□ □□□□□□□□□□□ □□□□□□□□□□□□ □□□□□□□□□□□
□□□□□ □□□□ □□□□□ □□□□ mtypes □ □□□□□□□ □□ greases.Sterilizes.Breaks □□□□□□□□ □□□□ emul sified.

□□□□□□□

:□□□□□ □□□□
□□□□□□□ □□□ □□□□□□□□ □□□□□□□ □□□ □□□□ □□□□□□□ □□□□□ □□□□□□□ □□□ □□□□□□□□ □□□□□□□ □□□□□□
□□□□□□□ □□ □□□□□ .□□□□□□□□ □□□□□□ □□□□ □□□□□□ □□□□□□ □□□□ □□□ □ □□□□□□□ □□□□□□ □□□□ □□ □□□□□□
.□□□□□□ □□□□ □□ □□□□□□□ □□□ □□□□ □□□□ □□□□□□□ □□ □□□□ □□□□□□□ □□□□□□

□□□□□□□□□□ □□□□□
□□□ □□□ □□□□□□ □□□□□ □□□□□□ □□□□□□□ □□□□□□ □□□□ □□□ □□□ □□□□□□ □□□□ □ □□□□□□□□□□ □□□
.□□□□□□□ □□□ □□□□□□□ □□□ □□□ □□□□ □ □□□ □□□□ □□□□ □□□□ □□□□□□ □□□□□ □□□□ □□□ □□□ □ □□□□□□□□□□
□□□ □□□ □□□□□□□□ □□□□ .□□□□□□ □□ □□□□□□□ □□□□□□□ □□□□□ □□□□ □□ □□□□□□ □□□ □□ □□□□□□ □□□□ □□
.□□□□□
.□□□□□□ □□□ □□ 2/3 □□□□□ □□□□□ □□□□ □□□□ □□□□ □□ □□□□□□□ □□ :□□□□□□
.□□□□□□ □□ □□□□□□ □□□ □□□□□ □□□ □□ □□□□□□□ □□□ □□□□□ □□□□□ □□□□□□ □□ □□□□□□ □□□□ □□
40 * 85 * 165 :(□□□□□ □□□□) □□□mm (L / W / H)
□□□□) □□□ outter): 175 * 95 * 50mm (L / W / H)
125 * 170 * 215 :□□□□□□□ □□□□□□□mm (L / W / H)
N.W: 0.65KG G.W: 0.85KG

PRODUCT APPLICATION

PRODUCT DISPLAY

PRODUCT SIZE

PRODUCT DETAILS

Model:BST-9050	Power： 30W/50	Voltage： 220V/240V
Volume： 0.5L	Frequency：40KHz	work time：8h

- ☑ Transducer with high power and strong effect.
- ☑ The volume is large enough for professional cleaning.
- ☑ With a forced cooling device, which can work very long.
- ☑ Safety circuit design, PCBA curing treatment.
- ☑ Switzerland introduced the advanced technology of elaborate design, using CPU control.
- ☑ Systemic use stainless steel to create, the appearance is very beautiful, high work efficiency, stable performance.
- ☑ Widely used in optical and clock parts, micro bearing, jewelry, medical equipment, electronic PCB board high requirements etc.

PRODUCT PHOTOGRAPH

FRONT

BEHIND

TOP

BOTTOM

PRODUCT PACKAGING

WEIGHT: 785G