

120V
3A



Specification parameters

model	BST-1203D
output voltage	0-120V
Output current	0-3A
input voltage	220V±10%50Hz
working temperature	0°C~40°C; Relative humidity:<80% RH
Storage temperature	-10°C~70°C; Relative humidity:<70% RH
Constant pressure state	Voltage stability $\leq 0.1\% \pm 3\text{mV}$ Low voltage: $0.2\sim 0.3\% \pm 3\text{mV}$
Load stability	$\leq 0.5\% \pm 3\text{mV}$
ripple noise	$\leq 30\text{mVrms}$ (effective value)
Constant current state	Current stability $\leq 0.2\% \pm 3\text{mA}$
Load stability	$\leq 0.2\% \pm 3\text{mA}$
ripple noise	$\leq 20\text{mA rms}$ (effective value)
Display accuracy	$0.5\% \pm 2$ words
Display resolution	0.01V/0.01V
electric current	0.01A/0.001A
Product size	252mm long x 170mm wide x 84mm high
Product weight	1.2kg
fuse value	3.15A



Professional high-precision output measurement

4 Digits Display Programmable DC power supply



Button control, more convenient operation

4-digit display



Key control



intelligence



Cooling fan



Low noise



security

VOLTAGE DISPLAY

CURRENT DISPLAY

POWER DISPLAY



< img src = "https://cdn.b2b.yjzw.net/files/96/img/2023/07/17/202307171819580177857.jpg" width = "100%" />

