□□□□□□□□

□□□□□□□□□□□□ □ □□□□□□ □□□□ .1
□□□□□□□ □□□□□□□ □□□□□□□ :□□□□□□□ □□□□□□□ 2.3
□□□□□□ □□□ □ □□□□□□□ □□□□□□ □□□□□ .3

□□□□□□□□□□□□ □□□□ □□□□
□□□□□□□□□□□□ □ □□□□□□ □□□□ .1
□□□□□□□ □□□□□□□ □□□□□□□ :□□□□□□□ □□□□□□□ 2.3
□□□□□□ □□□ □ □□□□□□□ □□□□□□ □□□□□ .3

□□□ □□□□□ □□ □□□□ □□□□ □□

□□□□□□□□□□□□ □□□□□□ □□□□□□□□ □□□□□□□□ □□ □□□□□□ .1

□□□□□□□□□ □□□□□ □□□□□□□□ □□□□□□ □□□□□□□ □□□□ □□□□□□ .2

□□□□ □□□□□□□□ □□□ .3

□□□□□□□□ □□□□□

.□□□□□□□□□□□□ □□□□□ □□□□□□□□ □□□□□□□ □□ □□□□□□□ □□□□□□ □□□□ □□□ .1

.□□□ □□□□□ □□□□ □□□ □□□□□□ □□ □□□□ □□□□□

.□□□□□ □□□□□ □□ □□□ □□□□□□□□ □□□□□ □□□□□□ □□□□□□ □□□□□ □□ □□□□□□ □□□□□ .2

□□□□□ □□□□ □□ □□□□□ □□□ □□□□□□ □□□□ □□□□□□□ □□ □□ □□□□□□ □□□ □□□□□ .3.

PRODUCT DISPLAY

PRODUCT SIZE

PRODUCT DETAILS




VENT
-40+105°C
LOW-PSR
1502E-1006

Applications: electronic circuit boards, home maintenance

Features: 1, the product uses high-tech all-metal aluminum material, high temperature, long service life
2, thread design, not slippery hand, heat-resistant Teflon nozzle, light and beautiful appearance.

Use: press the putter until you hear "Cha Cha" sound so far, the nozzle will have been used to iron soldering the solder joints, press the button to remove the solder.

PRODUCT PHOTOGRAPH

PRODUCT PACKAGING

WEIGHT:113G

FRONT

BACK