1.□□□□□□□□□□□□□□□□□□□□LED□□□□

2.□□□□□□□□□□□□□□□□□□

3.□□□□□□□□□□□

4.□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□state.Convenient□□□□□□□

5.Intelligent□□□□□□□□□□□100℃□□□□□□□□□□□□□□□□□□□□□□□□□□□□

6.□□□□□□□□□□□□□□□□□□□□□place.Brushless□□□□□□□□□□□□□

7.□□□□□□□□□□□□□□□□□□□□□

□□□□□

2□1□□□□□□□□PCB□IC SMT□SMD□□□□□□□

Specification

□□□□□	
□□□□□	AV110V / 220V 50HZ / 60Hz□
□□□□□	700□□
□□□□□	100°C□450℃□
□□□□□	□□□□□□□
□□□□□	120L /□□□□□□□
□□□□□	5mm□8□□10□□□□
□□□□	□□□□□□
S□ □□	
□□□□□	AC 26V±10□50HZ
□□□□□	60W
□□	200°C-480℃
□□	BST900 - M-T-□
□□□	□□□□□□

Description

Model:	BST-898D	Weight:	2.64kg
Name:	Combo free hot air gun + soldering station		
Features1	high-power,rapid heating,accurate and stable temperature		
Features2	The airflow is adjustable,the wind is heavy but soft		
Features3	Adopt sensor close loop,microcomputer control the temp -erature,LED display		
Features4	The solder iron heat rapidly, and can be back to tempera -ture quickly,which is good for lead-free soldering		

Description

Details



Temperature display of heat gun

Temperature display of solder iron



Up button/Down button
Changing-over button

Air volume regulator

Stainless steel nozzle
10mm,8mm,5mm, three different size

Air outlet
Screw diameter, the better the protection element

Open helper

IC extraction tool