

□ □

BEST-9050 30W / 50W□□□□□□□□□□□□

11

[illegible][illegible]

□□□□ - □□□□□□□□□□□□□□□□□□□□□□□□□□□□

□ □

1111

□□□□□

[illegible]

1111

[illegible][illegible]

2/3

[illegible]

165 \* 85 \* 40mm□□/□/□□

□□□□□□□□175 \* 95 \* 50mm□□/□/□□

215 \* 170 \* 125mm L / W / H

N.W 0.65KG G.W 0.85KG

## PRODUCT APPLICATION



## PRODUCT DISPLAY



## PRODUCT SIZE



## PRODUCT DETAILS



Model:BST-9050	Power: 30W/50	Voltage: 220V/240V
Volume: 0.5L	Frequency: 40KHz	work time: 8h

- ✓ Transducer with high power and strong effect.
- ✓ The volume is large enough for professional cleaning.
- ✓ With a forced cooling device, which can work very long.
- ✓ Safety circuit design, PCBA curing treatment.
- ✓ Switzerland introduced the advanced technology of elaborate design, using CPU control.
- ✓ Systemic use stainless steel to create, the appearance is very beautiful, high work efficiency, stable performance.
- ✓ Widely used in optical and clock parts, micro bearing, jewelry, medical equipment, electronic PCB board high requirements etc.

## PRODUCT PHOTOGRAPH



FRONT



BEHIND



TOP



BOTTOM





## PRODUCT PACKAGING

WEIGHT: 785G

