# STEREOMICROSCOPE

## MULTI-FUNCTION

# Product Usage

| | |
|---|---|
| Weight | 4.9kg |
| Objective lens | Continuous zoom 7x~45x |
| Eyepiece | Binocular wide angle WF10X |
| Power | 220v-50hz, 110v-50/60hz |
| Transformer | Built-in 0-12v, continuous dimming |
| Light source on the lamp | 12v/15w halogen lamp |
| Under light source | 12v/15w halogen lamp |
| Eyepiece holder | 45° inclination, 360° horizontal rotation<br>55-75mm pitch |
| Packing dimensions | 39.2 X 24.8 X 37cm |

## ▼CHARACTERISTICS

The microscope is suitable for a wide range of scenarios. Use a fully coated eyepiece to increase light transmission. A pure copper objective ensures image stability. Adjustable binoculars for different distances.

| Eyepiece | Standard configuration | | Additional large objective | | | | | |
|---|---|---|---|---|---|---|---|---|
| | | | 0.5X | | 1.5X | | 2X | |
| | Working distance100mm | | Working distance165mm | | Working distance45mm | | Working distance30mm | |
| | Magnification | Field of view | Magnification | Field of view | Magnification | Field of view | Magnification | Field of view |
| 10X/20 | 7X | 28.6 | 3.5X | 57.1 | 10.5X | 19 | 14X | 14.3 |
| | 45X | 4.4 | 22.5X | 8.9 | 67.5X | 3 | 90X | 2.2 |

# PRODUCT INFORMATION

# Suitable for various scenarios

LED halogen lamp

Variable power handle

Pure copper objective to ensure image stability

# ORIGINAL PHOTO



Adjustable binocular tube

# SHIPPING LIST

1.EYEPIECE PARTS
2. FOCUSING BRACKET
3.10/20X EYEPIECE X2
4. EYEPIECE COVER
5.THE RACK
6.INSTRUCTIONS
7.CHASSIS
8.THICK LARGE CARTON
9.THICKENED LARGE FOAM BOX