

# PRODUCT PHOTOGRAPH





# PRODUCT SIZE



## PRODUCT DISPLAY



Display bit: 3 1/2 bits

Accuracy: + 0.5%

Input impedance: 10M

Maximum display: 1999

Power supply: 9V (6f22)

Mode of operation: manual range

## PRODUCT PACKAGING

WEIGHT:330G



PARTS

PACKING

### Produktparameter

Grundfunktion	Reichweite.	Genauigkeit
Gleichspannung	200 mV/2 V/20 V/200 V/1000 V	±(0,5 %3)
Wechselstrom Spannung	200 mV/2 V/20 V/200 V/700 V	±(0,8 %5)
Gleichstrom	2mA/20mA/200mA/20A	±(0,8 %10)
Wechselstrom	2mA/20mA/200mA/20A	±(2,0 %5)
Widerstand	200Ω/2kΩ/20kΩ/200kΩ/2MΩ/20MΩ/200MΩ	±(0,8 %3)
Kapazität	200uF/20uF/2uF/200nF/20nF	±(2,5 %20)
Besondere Merkmale	9205M	
Dioden-, Audiontest	√	
Leitungsbruchalarm	√	
Unterspannungsanzeige	√	
Automatische Abschaltung	√(kann manuell eingestellt werden)	
Funktionsschutz	√	
200-mA-Dateisicherung	√	

20A-Dateisicherung	√
Stoßschutz	√
Eingangsimpedanz	10 MΩ
Betrieb	Manueller Bereich
Maximale Anzeige	1999
LCD	59×31mm
Leistung	9V (6F22)