1.Der Schweißdraht nimmt 60% Zinn 40% Blei, ist 0,3 bis 1,0 mm verfügbar; gute Benetzung, gute Lötbarkeit
2. Kleine Unreinheit, Diffusionskapazität gut
3. freundliche Produkte, nicht die Umwelt belasten.
4. Rauch ist klein, weniger Spritzer
5. Verwenden Sie für die gedruckte intensive Platine

Löten in TV, Radio oder normaler Haushaltsgeräte
Die Reparatur der normalen Haushaltsgeräte und Audio-Anlagen
Löten in Funktransponder, Instrument und Rechner und usw.

Description



Name:	Soldering wire	Brand:	BEST
Ingredient:	60% Tin, 40% lead	Weight:	500g
Melting:	183-190（℃）	Temperature:	280-320（℃）
Specification:	Φ0.5mm、0.6mm、0.8mm、1.0mm		
Features1:	Good wetting, good solderability.		
Features2:	Fewer impurities, the proliferation of good adhesion		
Features3:	Less smoke, less spatter, environmentally friendly products		
Features4:	Increase production speed.Reduce production costs		
Features5:	To welding-intensive printed circuit board.		

Size

HIGH QUALITY
BEST
SOLDER WIRE
55mm
Flux:2.25%
0.5mm
Sn Spec
AA%
W.T.: g
倍思特锡线
MADE IN CHINA
55mm