Descripción del producto

Lugar de origen: Shenzhen, China (continental)
Ampliación: 7-45 tims Zoom continuo
Ocular: campo ancho, dioptrías ajustables, WF10X / 22mm, WF 16X / 15mm
Objetivo: lente objetiva de 0.7-4.5 veces.
Etapa: Etapa deslizante mecánica de doble capa, triángulo de hierro que se mueve hacia arriba y hacia abajo
Descripción general del producto

Product Usage

N.W	4.7kg
Objective lens	Continuous zoom 7x~45x
Eyepiece	Binocular wide angle WF10X
Power	220v-50hz, 110v-50/60hz
Transformer	Built-in 0-12v, continuous dimming
Light source on the lamp	12v/15w halogen lamp
Under light source	12v/15w halogen lamp
Eyepiece holder	45° inclination, 360° horizontal rotation 55-75mm pitch

▼CHARACTERISTICS

The microscope is suitable for a wide range of scenarios. Use a fully coated eyepiece to increase light transmission. A pure copper objective ensures image stability. Adjustable binoculars for different distances.

Eyepiece	Standard configuration		Additional large objective					
			0.5X		1.5X		2X	
	Working distance100mm		Working distance165mm		Working distance45mm		Working distance30mm	
	Magnification	Field of view	Magnification	Field of view	Magnification	Field of view	Magnification	Field of view
10X/20	7X	28.6	3.5X	57.1	10.5X	19	14X	14.3
	45X	4.4	22.5X	8.9	67.5X	3	90X	2.2

PRODUCT INFORMATION

Fully coated eyepiece
for increased light transmission

Suitable for various scenarios

LED halogen lamp

LED light adjustment knob

Pure copper objective to ensure image stability

ORIGINAL PHOTO



Adjustable binocular tube

SHIPPING LIST

1.EYEPIECE PARTS
2. FOCUSING BRACKET
3.10/20X EYEPIECE X2
4. EYEPIECE COVER
5.THE RACK
6.INSTRUCTIONS
7.BLACK AND WHITE DOUBLE-SIDED MAT
8.THICK LARGE CARTON
9.THICKENED LARGE FOAM BOX