Descripción del producto:

Diámetro exterior: 6 mm Diámetro interno: 4mm

Material: oxígeno de alta calidad.

Vida: No menos de 50,000 juntas de soldadura.

SGS Protección Ambiental

900m-T-1C, 900M-T-2C, 900M-T-3C, 900M-T-1.2D, 900M-T-1.6D, 900M-T-2.4D, 900M-T-3.2D, 900M-

TI, 900m-TB, 900m-tk.etc.

936/937, 850 / 852/853/878/898/902, etc.

PRODUCT DISPLAY





Type D

Features: Welded with the front part of the head Application: suitable for the need for more than the amount of welding, such as: welding area, thick terminals, welding large welding environment.







Type K

Features: Are multi-purpose

Applicable to SOJ, PLCC, SOP, QFP

Type IS-I-B

Features: Bent / sharp / round

Application: Applicable to fine welding,
the case of small space



PRODUCT PHOTOGRAPH







WEIGHT:63.7G



International Brand
USER NOTES

1. The new iron tip before use must be on
the in. So that avoid oxidation, rust
and non-stick in.
2. Usually welding, the temperature
adjustment in the 250-350°C. Special
welding, such as welding shield and so
on, need to increase the temperature of
the control of the control of the control
diputment back 250-350 degrees after
welding. Otherwise, it easy to damage
iron and iron tip.
3. When you used up iron, please first
clean the iron tip in the twist sponge.
Then put the iron tip on the tin. So this
is not easy to make the iron tip black
and Longer used life.
4. BEST is first gold-plated iron tip in
China. Through the national testing to
private the control of the control of the control
plated, surface oxidation is more than
five times the traditional iron tip and
used life is ten times more than
domestic iron tips.

Environment Friendly Non-Pallution

FRONT

BACK

How to choose the right Iron tip



The correct choice of the size and shape of the tip is very important, the appropriate tip can make the work more efficient and increase the durability of the tip. The size of the tip and the heat capacity are directly related to the continuous welding, the use of the larger tip, the smaller the temperature drop. In addition, because the large soldering iron head heat capacity is higher, the relative use of welding can be relatively low temperature, the tip is not easy to oxidation, the relative extension of the service life. In general, the choice of the size of the tip does not affect the adjacent components as the standard. Choose to be able to fully contact with the welding geometric size, can improve the welding efficiency.

1, type I (pointed)

Features: tip tip tip;

Application: suitable for fine welding, or welding space is small, you can also modify the solder chip generated when the tin bridge. 2, type B (conical)

Features: B-type iron head without direction, the tip of the tip can be welded;

Application: suitable for general welding, regardless of the size of the solder joints, can use the B-type tip.

3, D type (one word approved Tsui shaped)

Features: welding part of the approved part;

Application: suitable for the need for more than the amount of welding, such as welding area, thick terminals, welding pad welding environment.

4, C type (horseshoe-shaped)

Features: with the tip of the tip of the tip of the welding, suitable for the need for more than the amount of welding; Application: C-type tip application range and D-type soldering head similar to, such as welding area, thick terminals, welding large applicable.

5, K-type (knife-shaped)

Features: the use of blade-shaped part of the welding, vertical or pull welding can be welded, are multi-purpose tip; Application: Applicable to SOJ, PLCC, SOP, QFP, power supply, grounding part of the components, to amend the tin bridge, connectors and other welding.