

120V
3A



Specification parameters

| | |
|-------------------------|---|
| model | BST-1203D |
| output voltage | 0-120V |
| Output current | 0-3A |
| input voltage | 220V±10%50Hz |
| working temperature | 0°C~40°C; Relative humidity:<80% RH |
| Storage temperature | -10°C~70°C; Relative humidity:<70% RH |
| Constant pressure state | Voltage stability $\leq 0.1\% \pm 3\text{mV}$ Low voltage: $0.2\sim 0.3\% \pm 3\text{mV}$ |
| Load stability | $\leq 0.5\% \pm 3\text{mV}$ |
| ripple noise | $\leq 30\text{mVrms}$ (effective value) |
| Constant current state | Current stability $\leq 0.2\% \pm 3\text{mA}$ |
| Load stability | $\leq 0.2\% \pm 3\text{mA}$ |
| ripple noise | $\leq 20\text{mA rms}$ (effective value) |
| Display accuracy | $0.5\% \pm 2$ words |
| Display resolution | 0.01V/0.01V |
| electric current | 0.01A/0.001A |
| Product size | 252mm long x 170mm wide x 84mm high |
| Product weight | 1.2kg |
| fuse value | 3.15A |



Professional high-precision output measurement 4 Digits Display Programmable DC power supply



Button control, more convenient operation 4-digit display



Key control



intelligence



Cooling fan



Low noise



security

VOLTAGE DISPLAY

CURRENT DISPLAY

POWER DISPLAY



< img src="https://cdn.b2b.yjzw.net/files/96/img/2023/07/17/202307171819580177857.jpg" width="100%" />

