

PRODUCT DISPLAY




PRODUCT SIZE


Front





Side




PRODUCT DETAILS





▲ PCB integrated motherboard double-sided chip technology



▲ High Power,Pure copper transformer

Rated working conditions

voltage	220v ± 10%
working environment	-10 °C ~ 40 °C Relative humidity: <90%
Storage environment	-20 °C ~ 40 °C Relative humidity: <80%
Corrugated factor	<= 0.5mvrs (5Hz-1MHz) Iomax> 1A
Features	Short circuit protection / overload protection / alarm function / continuity test / automatic recovery

Regulated working conditions

Power stability	<=0.01% + 2mV
Load stability	<=0.01% + 2mV (1max<1A)
Recovery Time	<=100us (maximum current <=3A)

Specifications

Model	PS-1502D+	PS-203D
Body weight	1.6KG	2.2KG
Dimensions	125MM*175MM*145MM	
Voltage and current	0-15V/0-2A	0-20V/0-3A
Features	Short circuit protection, automatic recovery, voltage test, on-off test	
GSM signal detection	 Can detect RF signals	
Overload protection current	2A	
Voltage display accuracy	0.1V	
Current display accuracy	0.01A	
Mobile signal strength indicator	Have	
Brush power supply function	No	
Smart cooling	No	Have

PRODUCT PACKAGING

WEIGHT:2.2KG



203D



Box
240mm*130mm*161mm



Instructions



Test lead test line



Power test line