



# Specification parameters

model	BST-1503T
output voltage	0-15V
Output current	0-3A
input voltage	220V±10% 50Hz
working temperature	0°C~40°C; Relative humidity:<80% RH
Storage temperature	-10°C~70°C; Relative humidity:<70% RH
Constant pressure state	Voltage stability $\leq 1\% \pm 3\text{mV}$
Load stability	$\leq 1\% \pm 3\text{mV}$
ripple noise	$\leq 30\text{mVrms}$ (effective value)
Constant current state	Current stability $\leq 0.2\% \pm 3\text{mA}$
Display accuracy	$0.5\% \pm 2$ words
Display resolution	0.01V/00.01V
electric current	0.01A/0.001A
Product size	215mm long x 85mm wide x 139mm high
Product weight	3.2kg
fuse value	3.15A



# Small machine



(Only 0.4 inches larger than a mobile phone)




Compared with other DC power supply, more compact, lighter, portable and Compact



Large volume and weight, inconvenient to use




**Intelligent Temperature Control: low noise, turn on when  $\geq 50^{\circ}\text{C}$**



**Large Capacitor**



**Single Phase Transformer: low ripple**




**CE FCC**

< img src="https://cdn.b2b.yjzw.net/files/96/img/2023/07/18/202307181416120199150.jpg" width="100%" />



# FOR PROFESSIONAL REPAIR OF MOBILE PHONES





DC POWER SUPPLY

USER IS MANUAL

(300W)

VER:02



BEST 德思特 BST-1503T SPS

15.0 V C.V  
USB 2.00 A

3A 15V  
0.5A 5V

VLOTAGE

POWER

- +

5V/2A