PRODUCT PHOTOGRAPH

.000
BEST
倍思特
DT-9205M
AUTO POWER OFF
POWER
Ω
200
2k
20k
200k
2M
20M
200M
hFE
A⎓
2m
20m
200m
20
20
200m
20m
A~
2m
200µ
20µ
2µ
200n
20n
200m
2
20
200
1000
700
200
20
2
V⎓
V~
F
IEC
1010
Cx
20A
mA
COM
VΩ
10sec
20AMAX
UNFUSED
200mA MAX
FUSED
AC750V MAX
DC1000V

PRODUCT SIZE

FRONT

BACK

PRODUCT DISPLAY

Display bit: 31/2 bits

Accuracy: + 0.5%

Input impedance: 10M

Maximum display: 1999

Power supply: 9V (6f22)

Mode of operation: manual range

PRODUCT PACKAGING

WEIGHT:330G

PARTS PACKING

Parametri del prodotto

Funzione di base	Allineare.	Precisione
Tensione CC	200 mV/2 V/20 V/200 V/1000 V	±(0,5%3)
Tensione CA	200 mV/2 V/20 V/200 V/700 V	±(0,8%5)
Corrente continua	2 mA/20 mA/200 mA/20 A	±(0,8%10)
Corrente alternata	2 mA/20 mA/200 mA/20 A	±(2,0%5)
Resistenza	200Ω/2kΩ/20kΩ/200kΩ/2MΩ/20MΩ/200MΩ	±(0,8%3)
Capacità	200uF/20uF/2uF/200nF/20nF	±(2,5%20)

Caratteristiche speciali	9205M
Diodo, test audio	√
Allarme interruzione linea	√
Display a bassa tensione	√
Spegnimento automatico	√(può essere impostato manualmente)
Protezione delle funzioni	√
Fusibile da 200 mA	√

Fusibile da 20A	√
Protezione dagli urti	√
Impedenza di ingresso	10MΩ
Operazione	Gamma manuale
Visualizzazione massima	1999
schermo LCD	59×31 mm
Energia	9 V (6F22)