

□□□□

| | |
|------|----------------------------|
| □□□□ | □□□□□□□□ |
| □□□ | □□□□ |
| □□□□ | □□&□□&□□□□ |
| □□□□ | 70°C×30□□93°C×15□□121°C×5□ |
| □□ | □□□□ |
| □□□□ | ODM/OEM |

SOLDER FLUX

Lead-free insulation



100g

Highly active / halogen free / lead free / non-resistive / non-conductive

Product Usage



| | |
|--------------|---------------------------------------------|
| MODEL | BST-559A |
| BRAND | BEST |
| PRODUCT NAME | Insulation solder paste |
| WEIGHT | 100g |
| TYPE | Strong activity,less residue easy to tin |

▼ characteristics

This product is widely used in PCB, BGA, CSP and welding repair. It is low halogen, can reach industry standards. With oxide layer for rapid removal of metal surfaces, components and strong metal bonding performance. Non-conductive insulation, fast wetting, less smoke, less residue.

PRODUCT INFORMATION

Welding requirements for a wide range of products



INSULATION SOLDER FLUX PASTE

BEST
倍思特

SOLDER FLUX
无铅绝缘助焊膏
BST-559A

RoHS

- Strong activity 活性强
- Halogen free 无卤素
- Lead free 无铅助焊膏
- No conductive 无阻值 不导电

SGS
MADE IN CHINA

TESTING EFFECT

LESS SMOKE
NO RESISTANCE
NON-CONDUCTIVE
STRONG ACTIVITY
STRONG WELDING
EASY TO TIN



PRODUCT SIZE



62.5MM



75MM

52MM