

# PRODUCT PHOTOGRAPH





# PRODUCT SIZE



## PRODUCT DISPLAY



Display bit: 3 1/2 bits

Accuracy: + 0.5%

Input impedance: 10M


Maximum display: 1999

Power supply: 9V (6f22)

Mode of operation: manual range

# PRODUCT PACKAGING

WEIGHT:330G



PARTS

PACKING

□□□□□□

□□□□	□□□	□□□
□□□□	200mV/2V/20V/200V/1000V	±(0.5%3)
□□□□	200mV/2V/20V/200V/700V	±(0.8%5)
□□□□	2mA/20mA/200mA/20A	±(0.8%10)
□□□□	2mA/20mA/200mA/20A	±(2.0%5)
□□	200Ω/2kΩ/20kΩ/200kΩ/2MΩ/20MΩ/200MΩ	±(0.8%3)
□□□□□□□	200uF/20uF/2uF/200nF/20nF	±(2.5%20)
□□□□□	9205M	
□□□□□□□□□□□□□□	√	
□□□□□□□□□□□	√	
□□□□□	√	
□□□□□□□□□	√(□□□□□□□)	
□□□□	√	
200mA□□□□□□□□	√	

20A□□□□□□□□

□□□□

□□□□□□□□

□□

□□□□

□□

□

√

√

10MΩ

□□□□□□□□

1999□

59×31mm

9V(6F22)