□□□ □□□ 3M □□ □□ □□□ □□□ □□ □□ □□□ 2mm-10mm 50m □□ □ □□ □□ □□

□□ □□

□□□□ □□□□□□ □□□ □□□ □□□□□□□ □□□ □□ □□□□.
□□□ □ □□□ □□□
□□ □□□, □□□, □□ □□□, □□
LCD □□ □□, □□ □, □□□, □□□ □□□ □□ □□ □□ □□□ □□

□□□:
□□ □□ : □□ □□ □□□
□□ : □ □□ □ □□, □□□ □ □□□
□□ □□ : 0.2cm, 0.3cm, 0.4cm, 0.5cm, 0.6cm, 0.7cm, 0.8cm, 0.9cm, 1cm
□□ : 5000cm
□□□ □□ □□□ : 120 □□□□
□□□ □□ □□ : 80 centi-degree
□□ : □□

PRODUCT DISPLAY

Customizable

Name:	3M9448 Transparent double-sided tape		
Thickness:	0.150 mm	**Colour:**	Transparent
Temperature resistance:	100°	**Weight:**	3mm/27G 6mm/101G
Material:	Non-woven substrate Acrylic glue		
Size:	Length:50M Width:customizable		

Features:

1. The acrylic acid pressure sensitive adhesive is applied on both sides of the non-woven substrate.
2. can be die cut.
3. can tear.
4. high temperature resistance.
5. The 3M trademark is printed on the release paper.

Strong viscosity

The tape will work better after 24 hours of sticking, and the longer the sticking time, the stronger the stickiness.

Safe, non-toxic and non-corrosive,

Strong viscosity, waterproof and moisture proof,
High temperature resistance, good resilience,
Easy to use, wide range of applications

3M Brand Tape