

3M 2mm-10mm 50m

00 00

0000 000000 000 000 00000000 0000 00 00000.
000 0 000 000
00 000, 000, 00 000, 00
LCD 00 00, 00 0, 000, 0000 0000 00 00 00 0000 00

000:
00 00 : 00 00 000
00 : 0 00 0 00, 000 0 000
00 00 : 0.2cm, 0.3cm, 0.4cm, 0.5cm, 0.6cm, 0.7cm, 0.8cm, 0.9cm, 1cm
00 : 5000cm
000 00 000 : 120 00000
000 00 00 : 80 centi-degree
00 : 00

PRODUCT DISPLAY



Customizable



Name:	3M9448 Transparent double-sided tape		
Thickness:	0.150 mm	Colour:	Transparent
Temperature resistance:	100°	Weight:	3mm/27G 6mm/101G
Material:	Non-woven substrate Acrylic glue		
Size:	Length:50M Width:customizable		

Features:

1. The acrylic acid pressure sensitive adhesive is applied on both sides of the non-woven substrate.
2. can be die cut.
3. can tear.
4. high temperature resistance.
5. The 3M trademark is printed on the release paper.

Strong viscosity

The tape will work better after 24 hours of sticking, and the longer the sticking time, the stronger the stickiness.



Safe, non-toxic and non-corrosive,

Strong viscosity, waterproof and moisture proof,
High temperature resistance, good resilience,
Easy to use, wide range of applications

