Features

1. DC □□ □□ □□

- □□ □□□□ □ □□□□□□□□.
- □□□ □□□ □□ □□□□□ 0□□ □□ □□ □□□ □ □□□□.
- □□□ □□ □ □□□ □□ □□□□□; □□ □□ □□□ □□ □□ □ □□ □□□ □□□□□□□.
- □□□ □□□ □□□ □□□ LED □□ □□□□.

2. DC □□ □□ □□ □□ □□ DC □□ □□ □□□ □□□□□

3. DC □□ □□ □□□ □□□ □□ □□□ □□□;

Application

DC □□ □□ □□□ □□ □□ □□ □□□, □□□ □□□ □□, □□ □□□ □□, □□ □□ □□ □ □□□ □□□□ □□□□□.

Specification

□□ □□	
□□ □□ □□	
□□ □□ □□:	220V 10 % ~ ± 50 □□□
□□ □□ □□:	0~15V
□□ □□ □□:	□□ 1A
□□ □□ □□:	15W
□□ □□□□□ □□□:	2.5 %
□□ □ □□:	≤(1)mVRMS□
□□:	□□, □□ □□□ □□

□□□ □□□ □□	
□□ □□:	0 ~ 15V □□□□ □□□□□ □□
□□ □□□:	≤0.01 % + 5 □
□□ □□□:	≤0.0(1)% +(2)MV
□□ □□:	≤100□□□(□□ □□ ≤□ 3A)
□□ □□□ □□□□ □□	
□□ □□:	□□□□□ □□ 0 ~ ~ 1A
□□ □□□:	≤0.2 % + 5mA
□□ □□□:	≤0.2 % + 10mA

□□ □□	
□□:	1.3KG
□□ □□:	17.4 * 9 * 15 CM
□□ □□:	76 * 28.5 * 46cm
□□:	(2)0 □□
□□□ □□:	28kg
□□:	M□□

□□ □ :

Features

Product Name：DC power supply

Product Type：BST-1501A

Body weight： 1. 3kg

Dimensions：106*141*150mm

Widely used in factory production lines, schools, maintenance, commissioning, laboratories and other places

Features introduced

1.Voltage :0-15V Current 0-1A；

2.Total power foot, high stability and reliable quality；

3.With short circuit protection, automatic recovery function;

Size

Length:141mm
Width：106mm
Height:150mm
BEST
PS-1501A
AUTOMAT
DC
OWER SUPPLY
短路保护
自动恢复
VOLTAGE
POWER
YOYICHN
CLASS2.5
0-15V
-1A

Products


Voltage output indicates (0-15V)
Current output indication (0-1A)
0-15V Export
Voltage Rotate button
Power switch indicator
Power switch
BEST
倍思特
PS-1501A
AUTOMAT
DC
POWER SUPPLY
短路保护
自动恢复
VOLTAGE
POWER
YOYICHN
CLASS2.5
0-15V
0-1A

Fuse
Power Cord
FUSE

Picture

Positive

Side

Back

Package

Detail

Voltage display

Voltage display accuracy: 2 small cell

Current Display

Current display accuracy: 2 small cell

0-15V output

Power key

After power on, press the switch is turned on to work, close to stop working

Voltage output / input mode conversion

Fused

Equipped with a fuse on the rear panel, the effective protection of the instrument, use more confidence