Features

1. □□□ □□ □□□□□ Cr-V □□□ □□□□□□ □□ □ □□□ □□□ □ □□□□.
2. □□□ □□ □□ □□, □□ HRC54-62
3. □□□ □□ □□□□□ 2 □ PVC □□□
4. 4.5 "□□
5. CE □□ □□ □□ □□

Specification

□□:	BEST-4 □□□ □□ □□
□□:	Cr-V □□ + PVC □□ □□
□□□:	□□□ □□□□ □□ 42-50HRC □□□□ □ □□□ 54-62HRC
□□ □□:	□□□
□□:	135mm
□□□:	12pcs / □□
N.W.	101g / pc
G.W .:	1.42kg / □□

Application

□□□ □□ □□□□□ □□□□□ □□ □□□, □□ □□□, □□ □□□, □□ □□, □□□□ □□ □□ □□ □□ □□□ □□□ □□□□□.

- □□□ □□□ □□ □□ □□.
- IC □□ □□ □ □□□ □□
- □□ □□.
- □□□ □ □□ □□ □ □□ □□.
- □□□□ □□ □□.
- D.I.Y □□□ % s □□ □□□ □□.

PRODUCT DISPLAY

PRODUCT SIZE

Material:high quality alloy steel(60CR-V)

Process:using repeated forging,the surface is polished after grinding and processing by precision machining

Hardness:the overall hardness is HRC38-42 the blade hardness is HRC56-62

Shear capacity:HRC20 below

Hard wire Φ1.5mm

soft copper wire,aluminum wire Φ0.1-2.0mm

PRODUCT DETAILS

Front

Back side



User manual

Warning

This model is not insulated tools. Please use it when power off.

Attention

- To protect user safe, please use protective glasses.
- As the cut material will fly out, make sure no one beside you and no easy damaged things beside you, then begin working.
- This product is not a dedicated pressure equipment.
- When stored, please assure the blade at the closed state and can not be touched by children.
- Do not let the plier tip rub something.
- Please do not directly touch the blade part with hand.
- Do not use in cutting hard materials and steel wire, etc.
- Do not use the pliers above its cutting capability and coarse wire.

PRODUCT PHOTOGRAPH

PRODUCT PACKAGING

WEIGHT:82G

FRONT

75MM



BACK