PRODUCT PHOTOGRAPH

.000
BEST
倍思特
DT-9205M
AUTO POWER OFF
POWER
Ω
200
2k
20k
200k
2M
20M
200M
hFE
A⎓
2m
20m
200m
20
20
200m
20m
A~
2m
200µ
20µ
2µ
200n
20n
200m
2
20
200
1000
700
200
20
2
V⎓
V~
F
IEC
1010
Cx
20A
mA
COM
VΩ
10sec
20AMAX
UNFUSED
200mA MAX
FUSED
AC750V MAX
DC1000V

PRODUCT SIZE

FRONT

BACK

PRODUCT DISPLAY

Display bit: 31/2 bits

Accuracy: + 0.5%

Input impedance: 10M

Maximum display: 1999

Power supply: 9V (6f22)

Mode of operation: manual range

PRODUCT PACKAGING

WEIGHT:330G

PARTS

PACKING

□□ □□□□

□□ □□	□□.	□□□
□□ □□	200mV/2V/20V/200V/1000V	±(0.5%3)
□□ □□	200mV/2V/20V/200V/700V	±(0.8%5)
□□ □□	2mA/20mA/200mA/20A	±(0.8%10)
□□ □□	2mA/20mA/200mA/20A	±(2.0%5)
□□	200Ω/2kΩ/20kΩ/200kΩ/2MΩ/20MΩ/200MΩ	±(0.8%3)
□□ □□	200uF/20uF/2uF/200nF/20nF	±(2.5%20)

□□□ □□	9205M
□□□□, □□□ □□□	√
□□□□ □□ □□	√
□□□ □□	√
□□ □□	√(□□□□ □□ □□)
□□ □□	√
200mA □□ □□	√

20A □□ □□	√
□□ □□	√
□□ □□□□	10MΩ
□□	□□ □□
□□ □□□□□	1999□
LCD	59×31mm
□	9V(6F22)