

BST-863

11

[illegible]

2 CH1, CH2, CH3 3 000 000 000 00, 00, 000 000 0 000 00 00 000 0 0000.

3. 鋼板の厚さ、鋼材の種類、溶接の種類、溶接部の形状等により、溶接部の強度は異なる。また、溶接部の強度は、溶接部の位置（端部、中央部）によっても異なる。

4. □□ □□ □□□ □□□ □□ □□□ □□□ □ □□□□.

5. 00 00 00, 00 000 000 00000000 00 00, LCD

□□□□. □□□ □□ □□□□ □□□□ □□ □□□ □□ □□ □□□□.

6. $\frac{1}{2} \times \frac{3}{4} \times \frac{5}{6} \times \frac{7}{8} \times \frac{9}{10} \times \frac{11}{12} \times \frac{13}{14} \times \frac{15}{16} \times \frac{17}{18} \times \frac{19}{20}$.

[illegible]

PRODUCT SIZE

Digital hot air desoldering station

- ✓ High power
- ✓ Automatic sleep
- ✓ Brushless turbine
- ✓ Warming up quickly
- ✓ Accurate and stable



PRODUCT FEATURES



Touch sensitive keys

Sensors closed loop, Zero-crossing triggering microcomputer temperature control, LCD touch screen. Heating up rapidly, the temperature accuracy and stability, without effect of the air flow, and truly achieved lead-free solder.





Model :	BST-863	Power :	1200W
Weight :	3.65kg	Display type :	LCD
Input Voltage :	AC 220V/110V 50/60Hz	Noise :	<45dB
Temperature Range :	100°C~550°C 212°F~1022°F		
Temperature Accuracy :	±1°C (Static)		
Air Volume Range :	1~100 level		
Mainframe Size :	188(L)*240(D)*135(H)mm		
Working Environment :	0°C~40°C/32°F~104°F		
Storage Environment :	-20°C~80°C/-4°F~176°F		
Storage Humidity :	35%~45%		

PRODUCT DETAILS



PRODUCT PACKAGING



BST-863



Bracket



Power line



Nozzle tip



Instruction manual



370mm*320mm*225mm

Packing box