

# PRODUCT PHOTOGRAPH





# PRODUCT SIZE



## PRODUCT DISPLAY



Display bit: 3 1/2 bits

Accuracy: + 0.5%

Input impedance: 10M

Maximum display: 1999

Power supply: 9V (6f22)

Mode of operation: manual range

## PRODUCT PACKAGING

WEIGHT:330G



PARTS

PACKING

### Product parameter

Basic function	Range.	Accuracy
DC voltage	200mV/2V/20V/200V/1000V	±(0.5%+3)
AC voltage	200mV/2V/20V/200V/700V	±(0.8%+5)
DC current	2mA/20mA/200mA/20A	±(0.8%+10)
AC current	2mA/20mA/200mA/20A	±(2.0%+5)
Resistance	200Ω/2kΩ/20kΩ/200kΩ/2MΩ/20MΩ/200MΩ	±(0.8%+3)
Capacitance	200uF/20uF/2uF/200nF/20nF	±(2.5%+20)
Special Features	9205M	
Diode, audion test	√	
Break line alarm	√	
Low voltage display	√	
Automatic shutdown	√(can be set manually)	
Function protection	√	
200mA file fuse	√	

20A file fuse	√
Shock protection	√
Input impedance	10MΩ
Operation	Manual Range
Maximum Display	1999
LCD	59×31mm
Power	9V (6F22)