

Specifications

Smart practical, with indicator light and power switch. Suitable for family use of all kinds of facility's repairment.

- 1.This glue gun adopt high-tech high temperature PTC.
- 2.High quality heating element, temperature rising rapidly, long service life.
- 3.Not influenced by voltage fluctuation, work normally under 100v-240v voltage.
- 4.Safety design, with Safety Electric Fuse inside to prevent overheating.
- 5.Insulation strength : 3750V/min

Model
Weight
Power
Voltage
Temperature
Insulation strength
Application
Time

Ø
m
z
l
e
d
i
a
m
e
t
e
r
:

D
i
a
m
e
t
e
r
:
5
m
g
l
u
e
s
t
i
c
k
:

E
x
t
r
a
g
r
a
m
i
n
n
m
e
l
t
v
o
l
u
m
e
:
D
e
r
i
v
a
t
i
v
e
t
e
m
p
e
r
a
t
u
r
e
:
A
p
p
c

PRODUCT APPLICATION



PRODUCT SIZE



PRODUCT DETAILS



PRODUCT FEATURES





Name: Hot melt glue gun

Model strips: 11mm

Muzzle: Alloy mouth

Voltage: 110V/220V

Model: BST-B-B

Weight: 294.3G

Power: 40W

Frequency: 50/60HZ

Feature1: Voltage limit is not built-in safety fuse, safe to use.

feature2: Ceramic PTC thermistor element heating speed, automatic thermostat, save energy

Feature3: Do not pour glue does not leak glue; glue gun tail retrofitting thermal insulation, glue gun and longer life

PRODUCT PACKAGING

WEIGHT:309G

190MM



265MM

FRONT

热熔胶枪

一、性能特点

1. 采用高科技陶瓷PTC热敏电阻发热元件, 升温速度快, PTC热敏电阻在温度达到设定温度时自动恒温, 节约能耗, 延长使用寿命。
2. 电气绝缘强度在通用3750V/分钟时不击穿, 在110V至240V交直流电压下可正常使用, 不受电压波动限制, 内置安全保险丝, 使用更安全。
3. 不倒胶和不漏胶: 枪尾尾部加装隔热装置, 延长胶枪使用寿命, 从而使胶枪寿命更长。

二、产品应用

1. 玩具模型, 2. 人造花、圣诞树, 3. 装饰品, 金属品, 4. 木制品、卡纸等, 5. 电子线路板, 6. 线路线材等。

三、使用方法

1. 本系列产品能适用直径Φ0.5-11.5mm的白、黄胶条。
2. 将胶条从胶枪尾部插入并送至枪管内, 插上电源预热5-8分钟后, 扣动扳机可挤出胶条并控制出胶量。
3. 在使用过程中, 如果插入的胶条一次未用完, 则胶条不用取出, 可供下次预热后继续使用。

四、注意事项

1. 应视产品系列选用相应规格的胶条, 如果使用了尺寸或者类型不符的胶条, 可能导致熔胶回流而堵塞胶枪。
2. 本产品为高温型胶枪, 工作时热熔胶枪的枪嘴和熔化的粘胶温度较高, 人体切勿触摸, 禁止在有熔化的粘胶温度较高、人体触摸、禁止在有易燃易爆的场所中使用。
3. 当胶枪通电数分钟以上不使用时, 胶条会往后融化, 此时严禁枪嘴向上, 以免胶液从尾部流出灼伤, 如需向上作业时请先扣动扳机3-4次。
4. 如果连续15分钟不打胶, 请切断电源, 以免胶条往后融化造成倒胶而损坏胶枪。
5. 由于胶枪内加装了耐用材料, 首次使用时可能会出现冒烟现象, 胶枪在使用30分钟后, 烟气自动消除。
6. 应保持枪尾部常浸的清洁, 以保证胶条顺畅进入枪管内。
7. 禁止将胶枪里的胶条从胶枪尾部取出。
8. 胶枪不用时应放置在通风干燥的地方, 禁止放在潮湿或有水的地方, 禁止放在小孩或儿童容易拿到的地方。
9. 本工具在不使用时必须放置在它的支架上。

USE YOUR HOT MELT GLUE GUN:

Insert the melt glue from glue the gun tail ministry, use 110v or 240v power source, and preheating 8 minutes, pull the trigger, then the glue can be controlled out.

CAUTION:

1. This glue gun is a higher temperature product, the melt glue diameter being applicable act as the gun of Φ0.5-11.5mm. If it uses the yellow melt glue or the dimensions is not conform to melt glue, it will be cause the melt glue recirculate to damage the glue gun.
2. The nozzle and the glue liquid are hot when they working. Men do not touch it.
3. Because the glue gun was made of higher temperature PTC, If the glue gun was not played glue successive 15 minutes, please cut off the electronic source to avoid the melt glue recirculate to damage the glue gun.

BACK