

Especificações

Tipo de caneta Ferro de solda a gás

1. Portable, use em qualquer lugar a qualquer momento
2. Nova energia: butano puro

BST-100 Tipo de caneta Ferro de solda a gás

Descrição do Produto

Instrução

1. Preencha com gás depois de confirmar que o interruptor foi desligado.
2. Preencha com gás como imagem 1. Lead o tanque de gás no orifício de enchimento e pressione para preencher.
3. Demora cerca de 10 segundos para completar o preenchimento. Aguarde alguns minutos para deixar o gás ficar firme antes de usar.
4. Por favor, pressione a entrada de ar levemente se houver ruído ZIZI após o enchimento.
5. Ligue o interruptor até ouvir o ruído ZIZI como imagem 2.
6. Mude o anel de chamar para frente como a imagem 3.
7. Fire a ponta com mais leve como foto 4
8. A flama se torna maior quando se move para '+', menor quando para '-'.
9. Começar a usar quando a chama desaparecer e a ponta fica vermelha. A chama não deve ser muito grande para prolongar a vida útil.
10. O comprimento da chama é de cerca de 12 mm a 15 mm.

Importante: Leia as instruções antes de usar e siga a seqüência de operação, de modo a evitar o perigo de uma operação incorreta.

PRODUCT DISPLAY



PRODUCT SIZE



PRODUCT FEATURES



Warning

- ▶ Please read the instruction before using and follow the operation sequence, so as to avoid the danger for improper operation .

Instruction

- ▶ 1.Fill with gas after confirming the switch has been turned off.
- ▶ 2.Fill with gas as picture 1.Lead the gas tank to the filling hole and press to fill.
- ▶ 3.It takes about 10 seconds to complete the filling. Wait several minutes to let the gas be steady before use.
- ▶ 4.Please press the air intake lightly if there is ZIZI noise after filling.
- ▶ 5.Turn on the switch until you hear ZIZI noise as picture 2.
- ▶ 6.Move the flameout ring forward as picture 3.
- ▶ 7.Fire the tip with lighter as picture 4
- ▶ 8.The flame become larger when move to '+',smaller when to '- '.
- ▶ 9.Begin to use when the flame disappears and the tip turns red. The flame should not be too large so as to prolong the service life.
- ▶ 10.The length of the flame is about 12 mm to 15 mm.



picture 1



picture 2



picture 3



picture 4

PRODUCT PHOTOGRAPH





PRODUCT PACKAGING

WEIGHT:72G



FRONT



BACK