

## **BST-2515A Solder Removedor de Pavio Desoldering Trança Fio Cabo Fluxo Fluxado**

### **Descrição do Produto**

Tipo: 100% novo

Comprimento: 1.5mm

Largura: 2.0mm

Revestido com fluxo de resina branca de água ultra alta purety.

Excelente transferência térmica para uma dessoldagem mais rápida e segura usando ferros de baixa temperatura.

Para usar: Coloque a mecha de solda sobre a área a ser dessoldada, aplique seu ferro de solda quente e a solda será absorvida na trança, repita com uma nova área de trança até que a junta esteja livre de excesso de solda.

### **Características:**

Fio de cobre da liga 1.Highquality da tecelagem da precisão.

2. Para a remoção de estanho na solda excede, resistência à oxidação e corrosão.

A condutibilidade 3.Thermal, efeito da lata é muito boa, sucção da lata limpa □ baixo residu.

4.Suitable para o circuito de precisão usando.

PRODUCT DISPLAY



PRODUCT SIZE



## PRODUCT FEATURES



FRONT



BACK



### Features:

1. High quality alloy copper wire from the precision weaving.
2. For the removal of tin in the excess solder, resistance to oxidation and corrosion.
3. Thermal conductivity, tin effect is very good, tin suction clean. Low residue.
4. Suitable for precision circuit using.

PRODUCT PHOTOGRAPH

WELGHT:8.5G

LENGTH:1.5M  
WIDTH:1.5MM





