1.O fio de solda adota 60% de estanho 40% de chumbo, 0,3-1,0 mm é disponível; bom umedecimento, boa soldabilidade
2. Pouco a impureza, a capacidade de difusão do bem
3. produtos amigáveis, não poluem o meio ambiente.
4. O fumo é pequeno, menos respingos
5. Use para a placa de circuito impresso intensiva

Solda em televisão, rádio ou aparelhos domésticos normais
Reparação dos aparelhos domésticos normais e instalações de áudio
Solda em transponder de rádio, instrumento e calculadora e etc.

Description



Name:	Soldering wire	Brand:	BEST
Ingredient:	60% Tin, 40% lead	Weight:	500g
Melting:	183-190（℃）	Temperature:	280-320（℃）
Specification:	Φ0.5mm、0.6mm、0.8mm、1.0mm		
Features1:	Good wetting, good solderability.		
Features2:	Fewer impurities, the proliferation of good adhesion		
Features3:	Less smoke, less spatter, environmentally friendly products		
Features4:	Increase production speed.Reduce production costs		
Features5:	To welding-intensive printed circuit board.		

Size

HIGH QUALITY
BEST
SOLDER WIRE
55mm
Flux:2.25%
0.5mm
Sn Spec
AA%
W.T.: g
倍思特锡线
MADE IN CHINA
55mm