SMART PHONE POWER CORD

DC 4.2~4.8V

0 ~ 3 A

Data simulation

Digital display screen

Applicable for iPhone/Android



No wiring required

Product Specifications

Name	Phone power cord
Model	BES-063
Input voltage	DC 4.2V~4.8V
Output current	0-3A
Shell	ABS+PC
Package	Plastic storage box
Package dimensions	217*100*42mm
G.W.	320g


Upgraded version
Applicable for iPhone/Android
POWER
4.5013 V
0.0000 A
CURRENT
BEST
倍思特
BST-063
TEST CABLE
KB-LK
RESET
ON/OFF
START
WARNING
The input voltage must not be higher than 4.8V or lower than 4.2V, otherwise the external output equipment will not work properly or burn out.
注意：输入电压不能高于4.8V或低于4.2V，否则将导致外接输出端不能正常工作或烧毁。
5 Digit display
Display current and voltage
4 USB interface
Multiple phone detection

6G
6P
6S-6SP
7G
7P
8P
X
Android
Android
Alligator clip

POWER
CURRENT
4.4548 V
0.0000 A
BEST
倍思特
BST-063
TEST CABLE
KB-LK
RESET
ON/OFF
START
WARNING
The input voltage must not be higher than 4.8V or lower than 4.2V, otherwise the external output equipment will not work properly or burn out.
注意：输入电压不能高于4.8V或低于4.2V，否则将导致外接输出端不能正常工作或烧毁。
Power Indicator
Work indicator
Voltage
Current
ON/OFF
Start up/Reset
Power negative port
Power positive interface

Product Configuration and Usage



Short circuit protection, intelligent identification, support mainstream mobile phone models.

Product Pictures

BST-063
TEST CABLE
RESET
KB-LK
START
ON/OFF
WARNING

BEST 1505T
通讯测试高级直流稳压电源
DC POWER SUPPLY FOR COMMUNICATION TEST
V
A
85C1
85C1-A
GSM
PHS
CDMA
RF
-04.5 V
VOLTAGE
5A
1A
电压
测量
输出
显示
5V锁定
15V
5V
USB
5V 2A
POWER
I
0
4.5013 V
0.0000 A
BST-063
TEST CABLE
KB-LK
RESET
ON/OFF
START
WARNING

BEST 1505T
通讯测试高级直流稳压电源
DC POWER SUPPLY FOR COMMUNICATION TEST
V
A
85C1-A
GSM
PHS
CDMA
40
35
25
20
RF
-04.5 V
5A
1A
5V
15V
POWER
CURRENT
4.5025 V
0.5000 A
BST-063
TEST CABLE
KB-LK
RESET
ON/OFF
START
WARNING
主板

Product Dimension



Package Dimension

G.W.:320g