



1. 採用最先端のLED adopts 高効率のLEDを採用し、省電力・省スペースを実現し、LED
 2. 採用最先端のLED, 高効率のLEDを採用し、省電力・省スペースを実現し、LED
 3. 採用最先端のLED, 高効率のLEDを採用し、省電力・省スペースを実現し、LED
 4. 採用最先端のLED, 高効率のLEDを採用し、省電力・省スペースを実現し、LED state.Convenient 採用最先端のLED, 高効率のLEDを採用し、省電力・省スペースを実現し、LED
- 採用最先端のLED 5.Intelligent 採用最先端のLED, 高効率のLEDを採用し、省電力・省スペースを実現し、LED
6. 採用最先端のLED, 高効率のLEDを採用し、省電力・省スペースを実現し、LED place.Brushless 採用最先端のLED, 高効率のLEDを採用し、省電力・省スペースを実現し、LED
 7. 採用最先端のLED, 高効率のLEDを採用し、省電力・省スペースを実現し、LED

採用最先端のLED:

2 in 1 採用最先端のLED, 高効率のLEDを採用し、省電力・省スペースを実現し、LED PCB, IC SMT, 採用最先端のLED SMD 採用最先端のLED, 高効率のLEDを採用し、省電力・省スペースを実現し、LED

Specification

採用最先端のLED	
採用最先端のLED:	AV110V / 220V 50Hz / 60Hz
採用最先端のLED:	700w
採用最先端のLED:	100 ° C ~450 ° C
採用最先端のLED:	Brushless
採用最先端のLED:	120L / 採用最先端のLED (採用最先端のLED)
採用最先端のLED:	8mm 10mm 5mm
採用最先端のLED:	採用最先端のLED
S採用最先端のLED	
採用最先端のLED:	AC 26V ± 10% 50Hz
採用最先端のLED:	60W
採用最先端のLED:	200 ° C-480 ° C
採用最先端のLED:	BST900-M-T-I
採用最先端のLED:	採用最先端のLED

Description



Model: BST-898D

Weight: 2.64kg

Name: Combo free hot air gun + soldering station

Features1 high-power,rapid heating,accurate and stable temperature

Features2 The airflow is adjustable,the wind is heavy but soft

Features3 Adopt sensor close loop,microcomputer control the temperature,LED display

Features4 The solder iron heat rapidly, and can be back to temperature quickly,which is good for lead-free soldering

Description





Temperature display of heat gun



Temperature display of solder iron



Up button/Down button
Changing-over button



Air volume regulator



Stainless steel nozzle
10mm,8mm,5mm, three different size



Air outlet
Screw diameter, the better the protection element



Open helper



IC extraction tool

