

Features

- 1 採用 ESD PPS 材料
- 2: 表面電阻率 $1 \times 10^9 \Omega$ / m
- 3: 耐熱性、耐衝擊性、耐腐蝕性
- 4: 採用 PCB, 表面電阻率, 耐熱性, 耐腐蝕性 Beaty

優點

1. 表面電阻率 $1 \times 10^9 \Omega$ / m
2. 耐熱性、耐衝擊性、耐腐蝕性
3. 採用 PCB, 表面電阻率, 耐熱性、耐腐蝕性
4. 採用 PCB, 表面電阻率, 耐熱性、耐腐蝕性

ESD

ESD 測試方法

1. 表面電阻率 $1 \times 10^9 \Omega$ / m
2. 耐熱性、耐衝擊性、耐腐蝕性
3. 採用 PCB, 表面電阻率 260°C
4. 採用 PCB, 表面電阻率 $200 \sim 240^\circ \text{C}$
5. 耐熱性、耐衝擊性、耐腐蝕性
6. 採用 PCB, 表面電阻率, 耐熱性、耐腐蝕性

Specification

產品名稱:	表面電阻率 $1 \times 10^9 \Omega$ / m
型號:	BST-00
材料:	表面電阻率 + PPS ESD 材料
規格:	表面電阻率
表面電阻率:	表面電阻率
硬度:	> HRC40 (鋼) 表面電阻率 (鋼)
厚度:	129mm
重量:	30g (表面電阻率)
數量:	17pcs
包裝重量 / 數量:	590g
尺寸 (L * W * H):	204 * 163 * 45mm
尺寸 (L * W * H):	52 * 42 * 34cm
重量:	19.4kg

Size



Picture

Side



Side



Top



Top



Local



Pack



Details



Using high-precision equipment,
laser type



4 screw fix head, robust and easy
replacement



Head use high-strength, anti-
-static PPS plastic

When two tip are folded,
smooth seamless

ABOUT US

Shenzhen Jinliyang Technology Co., Ltd is a professional large-scale manufacturer of Power bank and repairing tools for communication products.

With 20 years abundant experience in manufacturing and wholesale industry, we have set up subsidiary companies one by one in some cities in China and built up a complete sales network. Depending on quality products and the tenet of honesty and credit, we have established good long term cooperation with customers all over the world. Our brands "BEST" and "SUYOU" have been know abroad, and CE and Rohs certificates of our products are approval.

"Sincerity oriented and credibility is the first" is our service tenet.

