

Features

1. 採用 adops ESD PPS 材料
2. 電阻率: $1 \times 10 \Omega$ 電阻率: 47j / m
3. 採用 PPS 材料
4. 採用 PCB, 採用 Beaty

優點

1. 採用 PPS 材料
2. 採用 PPS 材料
3. 採用 PPS 材料, 採用 PPS 材料
4. 採用 PPS 材料

ESD

ESD 材料

1. 採用 PPS 材料
2. 採用 PPS 材料
3. 採用 PPS 材料 260 ° C
4. 採用 PPS 材料 200 ~ 240 ° C
5. 採用 PPS 材料
6. 採用 PPS 材料

Specification

材料:	採用 PPS 材料 (採用 PPS 材料)
型號:	BST-259A
電阻率:	採用 PPS 材料 + PPS ESD 材料
電阻率:	採用 PPS 材料
電阻率:	採用 PPS 材料
電阻率:	> HRC40 ° (採用) 採用 PPS 材料 (採用)
電阻率:	129mm
電阻率:	27.9g (採用)
電阻率:	17pcs
電阻率 / 電阻率:	554g
電阻率:	204 * 163 * 45mm(L * W * H)
電阻率:	52 * 42 * 34cm(L * W * H)
電阻率:	18kg

Size



Picture

Side



Side



Top



Top



Local



Pack



Details



Using high-precision equipment,
laser type



4 screw fix head, robust and easy
replacement



Head use high-strength, anti-
-static PPS plastic

When two tip are folded,
smooth seamless

ABOUT US

Shenzhen Jinliyang Technology Co., Ltd is a professional large-scale manufacturer of Power bank and repairing tools for communication products.

With 20 years abundant experience in manufacturing and wholesale industry, we have set up subsidiary companies one by one in some cities in China and built up a complete sales network. Depending on quality products and the tenet of honesty and credit, we have established good long term cooperation with customers all over the world. Our brands "BEST" and "SUYOU" have been know abroad, and CE and Rohs certificates of our products are approval.

"Sincerity oriented and credibility Is the first" is our service tenet.

