

Features

- [illegible]

□ □ □ □ □ □ □ □ □ □

1.
2.
3. ,
4.

1111

ESD □□□□□□□□□□□□□□□□□□□□

1. 試験片の準備 (材料の採取、形状の調整)
2. 試験片の乾燥 (水分の除去)
3. 試験片の加熱 (260 °C)
4. 試験片の冷却 (200 ~ 240 °C まで)
5. 試験片の冷却 (室温まで)
6. 試験片の測定 (長さ、重量、断面形状)

Specification

品名:	防静电周转箱(防静电周转箱)防静电
型号:	BST-2A
材质:	防静电PPS + PPS ESD 防静电材料
颜色:	蓝色
规格尺寸:	防静电周转箱规格尺寸
重量:	> HRC40 ° (厚度) 防静电周转箱重量 (kg)
长度:	129mm
宽度:	27.1g (防静电箱)
高度:	17pcs
容量 / 重量:	540.7g
内部尺寸:	204 * 163 * 45mm(L * W * H)
外部尺寸:	52 * 42 * 34cm(L * W * H)
总重量:	16kg

Size



Picture

Side



Side



Top



Top



Local



Pack



Details



Using high-precision equipment,
laser type



4 screw fix head, robust and easy
replacement



Head use high-strength, anti-
static PPS plastic

When two tip are folded,
smooth seamless

ABOUT US

Shenzhen Jinliyang Technology Co., Ltd is a professional large-scale manufacturer of Power bank and repairing tools for communication products.

With 20 years abundant experience in manufacturing and wholesale industry, we have set up subsidiary companies one by one in some cities in China and built up a complete sales network. Depending on quality products and the tenet of honesty and credit, we have established good long term cooperation with customers all over the world. Our brands "BEST" and "SUYOU" have been know abroad, and CE and Rohs certificates of our products are approval.

"Sincerity oriented and credibility Is the first" is our service tenet.

