

PRODUCT PHOTOGRAPH





PRODUCT SIZE



PRODUCT DISPLAY



Display bit: 3 1/2 bits

Accuracy: + 0.5%

Input impedance: 10M


Maximum display: 1999

Power supply: 9V (6f22)

Mode of operation: manual range

PRODUCT PACKAGING

WEIGHT:330G



PARTS

PACKING

□□□□□□□□□□□□□□□□

□□□□□□□□□□□□□□

□□□□□□□□□□□□□□□□

□□□□□□□□□□□□□□□□

□□□□□□□□

□□□□□□□□□□□□□□□□

□□□□□□□□□□

□□□□□□□

□□□□□□□□□□□□

□□□□□, □□□□□□□□□□□□□□□□

□□□□□□□□□□□□□□□□

□□□□□□□□□□□□□□□□

□□□□□□□□□□□□□□□□

□□□□□□□□□□□□□□□□

□□□□□□□□ 200mA

□□□□□□□.

200mV/2V/20V/200V/1000V

200mV/2V/20V/200V/700V

2mA/20mA/200mA/20A

2mA/20mA/200mA/20A

200Ω/2kΩ/20kΩ/200kΩ/2MΩ/20MΩ/200MΩ ±(0.8%3)

200uF/20uF/2uF/200nF/20nF

9205M

□□□□□□□□□□

±(0.5%3)

±(0.8%5)

±(0.8%10)

±(2.0%5)

±(0.8%3)

±(2.5%20)

√ (□□□□□□□□□□□□□□□□□□□□)

□□□□□□□□ 20A

□□□□□□□□□□□□□□

□□□□□□□□□□□□□□

□□□□□□□□□□

□□□□□□□□□□□□

□□□□□□□□

□□□□

10MΩ

□□□□□□□□□□□□

1999

59×31□□

9V (6F22)